



- THREADED CONNECTION
- SOCKET CONNECTION

TECHNICAL DATA					
MODEL NO.	SIZE	'A'	'B'	'C'	'D'
RPBV-075	3/4"	1-1/4"	2-3/4"	3-3/8"	5-7/8"
RPBV-100	1"	1-3/8"	2-3/4"	4-3/4"	4-15/16"
RPBV-125	1-1/4"	1-5/8"	3"	5-1/4"	4-15/16"
RPBV-150	1-1/2"	2"	4"	6-3/8"	6-9/16"
RPBV-200	2"	2-3/8"	4-3/4"	7-3/8"	7-3/4"
RPBV-300	3"	3-3/4"	7-1/2"	10-1/8"	11-5/8"

SPECIFICATION DATA: PVC 'True-Union' type Ball Valve, featuring PVC Schedule 80 construction, full port ball, EPDM 'O' rings, Teflon ball seats, heavy stem with double 'O'-rings and Socket or (F) N.P.T. end connections.

DESIGN/APPLICATION DATA: RPBV Series PVC ball valves are designed for use in fountain systems for isolation and flow regulation of nozzles and smaller diameter piping systems. The compact, streamlined design allows for ease of handling, installation and operation.

NOTE: Due to continuing product improvement program, Roman Fountains reserves the right to change the specifications without notice.

DRAWING NO.
3.708