


(877) 794-1802



PLAN VIEW



ELEVATION VIEW

TECHNICAL DATA						
MODEL NO.	CUT POINTS	LIGHT COLOR	OUTPUT LUMENS	MAXIMUM LENGTH	POWER USAGE	LED CHIPS
RFL-SL-WW-24VDC-XX	4"	"WARM" (3500K)	124/FT.	32 FT.	1.46 WATTS/FT	18/FOOT
RFL-SL-CW-24VDC-XX	4"	"COOL" (3800K)	124/FT.	32 FT.	1.46 WATTS/FT	18/FOOT
RFL-SL-DW-24VDC-XX	4"	"DAY" (7000K)	124/FT.	32 FT.	1.46 WATTS/FT	18/FOOT

IMPORTANT NOTE: "XX" in Model No. above denotes length in inches



SPECIFICATION DATA: 24VDC; U.L. Listed LED Linear Strip Lighting; submersible/waterproof IP68 rated with 120 beam angle; SMD 3528 LED chips; custom cut per project in 4" increments; 25' cable length. Mount with silicone adhesive caulk (not included). Lamp life: up to 50,000 hrs.

- NOTES:**
- 24VDC Power supply required to operate fixtures. Contact factory for requirements.
 - Due to our continuing product improvement, Roman Fountains reserves the right to change the specifications without notice.

DRAWING NO.
5.116